

CAN

 Bluetooth™ 5

SCHILDKNECHT
SMART DATA COMMUNICATION



Provided and tech-supported in the U.S. by
Aunex Inc. | 725 Prudden Street | Lansing | MI 48906
phone 863 303 8038 - www.aunex.io - support@aunex.io




DATAEAGLE® 6000
WIRELESS CAN



WIRELESS CAN - DATAEAGLE 6000

General information

The [DATAEAGLE 6000](#) series was especially designed for the transparent transmission of CAN using radio technologies. To increase the performance of the radio link, the transmitted CAN identifiers can be set in a whitelist.

- Optimized for devices with CAN interface
- Plug and Play - no device configuration necessary
- Up to 3 km range



BLUETOOTH 5 IN DATAEAGLE 6730

Very fast data transmission via radio

The use of modern Bluetooth 5 wireless technology in the DATAEAGLE 6730 enables the highest requirements in terms of speed and latency. This makes the DATAEAGLE 6730 is particularly suitable for high-performance and safety applications.

- 2 times faster data transmission with minimal latency
- State-of-the-art safety through 128 bit AES encryption



APPLICATION EXAMPLES

Versatile

We have been successfully equipping industrial plants with our radio data transmission system for over 40 years. On our website you will find numerous [practical examples](#) and an overview of our [industry sectors with reports about wireless solutions](#).

- Substitute of conductor lines
- Substitute of trailing cables and cable chains
- Substitute of optical data transceivers
- Crane systems
- Warehouse systems
- Automotive industry
- Transport vehicles
- Water, wastewater, waste and raw material management
- Engineering
- Lifts, inclined lifts and cable cars
- Oil and gas industry
- Steel and cement plants
- Stage technology



WIRELESS CAN - DATAEAGLE 6000

Differences at a glance

Product	Frequency	Typical Distance*	Max. Radio Slaves	Protection class
Compact 6730	2,4 GHz Bluetooth 5	300 m	4	IP20
X-treme 6730	2,4 GHz Bluetooth 5	300 m	4	IP65
Compact 6330 Compact 6340	869 MHz 915 MHz	3000 m	4	IP20
X-treme 6330 X-treme 6340	869 MHz 915 MHz	3000 m	4	IP65

* Note on typical distance for data radio systems

The range of a radio data transmission solution depends on the quality and type of antennas. Depending on the choice of antenna, the range of the radio solution can therefore vary. With a directional antenna, the typical distance of 300 meters can be significantly increased. Contact us for [personal advice](#) or download the [white paper on antennas](#).





DATAEAGLE COMPACT 6730

Technical data



o GENERAL

Voltage supply	24 V DC
Connection Voltage supply	Terminal clamps
Power consumption	100 mA
Fixing	DIN rail mounting
Protection class	IP20
Temperature range	-20...+60 °C
Conformity	CE, FCC, IC
Weight	130 g
Width	22,5 mm
Height	99 mm
Depth	114,5 mm
Color	Black

o RADIO TECHNOLOGY

Frequency	2,4 GHz Bluetooth 5
Transmitting power	8 dBm
Max. Number radio slaves	4
Range Indoor	100 m
Range Outdoor	300 m
Antenna connection	SMA Connection - 50 Ohm

o INTERFACE

Max. CAN Transmission rate	500 kBit/s
CAN Connection	9 pol. SUB-D

o ORDER NUMBER

11268

- o [Here you find all informations about antennas and accessories](#)
- o [Go back to product overview](#)





DATAEAGLE X-TREME 6730

Technical data



GENERAL

Voltage supply	24 V DC
Connection Voltage supply	M12, A-coded
Power consumption	100 mA
Fixing	4-hole screw fastening
Protection class	IP65
Temperature range	-20...+60 °C
Conformity	CE, FCC, IC
Weight	280 g
Width	88 mm
Height	120 mm
Depth	42 mm
Color	Black

RADIO TECHNOLOGY

Frequency	2,4 GHz Bluetooth 5
Transmitting power	8 dBm
Max. Number radio slaves	4
Range Indoor	100 m
Range Outdoor	300 m
Antenna connection	SMA Connection - 50 Ohm

INTERFACE

Max. CAN Transmission rate	500 kBit/s
CAN Connection	M12, A-coded

ORDER NUMBER

11278

- [Here you find all informations about antennas and accessories](#)
- [Go back to product overview](#)





DATAEAGLE COMPACT 6330 / 6340

Technical data



○ GENERAL

Voltage supply	24 V DC
Connection Voltage supply	Terminal clamps
Power consumption	100 mA
Fixing	DIN rail mounting
Protection class	IP20
Temperature range	-20...+60 °C
Conformity	CE (869 MHz), FCC (915MHz)
Weight	160 g
Width	22,5 mm
Height	99 mm
Depth	114,5 mm
Color	Black

○ RADIO TECHNOLOGY

Frequency	869 MHz or 915 MHz
Transmitting power	500 mW (EIRP)
Range Indoor	300 m
Range Outdoor	1000 - 3000 m
Antenna connection	SMA Connection - 50 Ohm

○ INTERFACE

Max. CAN Transmission rate	500 kBit/s
CAN Connection	9-pin SUB-D

○ ORDER NUMBER

DATAEAGLE Compact 6330 (869 MHz)	11145
DATAEAGLE Compact 6340 (915 MHz)	11159

- [Here you find all informations about antennas and accessories](#)
- [Go back to product overview](#)

CAN



DATAEAGLE X-TREME 6330 / 6340

Technical data



GENERAL

Voltage supply	24 V DC
Connection Voltage supply	M12, A-coded
Power consumption	100 mA
Fixing	4-hole screw fastening
Protection class	IP65
Temperature range	-20...+60 °C
Conformity	CE (869 MHz), FCC (915MHz)
Weight	300 g
Width	88 mm
Height	120 mm
Depth	42 mm
Color	Black

RADIO TECHNOLOGY

Frequency	869 MHz or 915 MHz
Transmitting power	500 mW (EIRP)
Range Indoor	300 m
Range Outdoor	1000 - 3000 m
Antenna connection	SMA Connection - 50 Ohm

INTERFACE

Max. CAN Transmission rate	500 kBit/s
CAN Connection	M12, A-coded

ORDER NUMBER

DATAEAGLE X-treme 6330 (869 MHz)	11373
DATAEAGLE X-treme 6340 (915 MHz)	11375

- [Here you find all informations about antennas and accessories](#)
- [Go back to product overview](#)

CAN



Provided and tech-supported in the U.S. by
Aunex Inc. | 725 Prudden Street | Lansing | MI 48906
phone 863 303 8038 - www.aunex.io - support@ aunex.io



Schildknecht AG

Haugweg 26

D-71711 Murr

Tel. + 49 7 144 - 89 71 80

Fax + 49 7 144 - 89 71 82 9

www.schildknecht.ag

office@schildknecht.ag